



TECHNICAL SHEET FA 70 025 50

SELF EVACUATION KIT 50 M



FA 70 005 00



FA 70 021 00



FA 50 302 22B (x 4)



+

FA 70 010 99 (50) +
FA 50 302 22BFA 60 005 00
(x 2)

FA 90 106 00

This simple and light self-evacuation kit is designed to be used from an identified workstation at height, where a fall arrest harness may not be required. This system allows the evacuation of the user downwards.

This kit is composed of:

- A rescue triangle **FA 70 005 00** with dorsal D-Ring for the guiding of the evacuation and shoulder straps made of elastic webbing,
- A descender made up of Aluminium alloy **FA 70 021 00** with self-braking system and safe locking eye, conform to EN 341,
- 4 Keylock Triple Action-locking karabiners **FA 50 302 22B**, conform to EN 362,
- A semi-static rope, length 50 m **FA 70 010 99 (50)**, conform to EN 1891, with 1 Keylock karabiner **FA 50 302 22B**,
- 2 anchorage webbing slings **FA 60 005 15**, length 1,50 m, conform to EN 795,
- A cylindrical PVC transport bag **FA 90 106 00**.

This kit is also available in a 20 m version (FA 70 025 20) and in a 30 m version (FA 70 025 30).



Weight:

kg

KRATOS SAFETY

ZI les Portes du Dauphiné
4, rue de l'Aigue
69780 Saint Pierre de Chandieu – FRANCE

Tel. : +33 (0)4 72 48 78 27

Fax. : +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

HS CODE

CARTON SIZE / PIECE

ARTICLE 11 GB07/73551

SGS United Kingdom Ltd., N°0120

Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom