




FA 20 104 00

FA 20 104 10

FA 20 104 20



FA 20 104 30

FA 20 104 40

FA 20 104 50



HS CODE
56090090
CARTON SIZE / PCS.
FA 20 104 10 : 60 x 40 x 24 cm / 10 FA 20 104 20 : 40 x 40 x 24 cm / 5 FA 20 104 30 : 60 x 40 x 24 cm / 5 FA 20 104 40 : 80 x 40 x 24 cm / 5 FA 20 104 50 : 80 x 40 x 24 cm / 5
AET N°2777/10847-02/E01-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.02
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland
AET (UKCA) N°AB0321/16011-01/E01-01
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
MODULE D 11 IN14/14003
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom


REF.	FA 20 104 10	FA 20 104 20	FA 20 104 30	FA 20 104 40	FA 20 104 50
LG.  KG	10m	20 m	30 m	40 m	50 m
CE	MAX. 140 KG				
MAT.	Polyester Ø 12 mm				
	---				
	---				
R(kN)	15 kN				
	1.71 kg	2.76 kg	3.81 kg	4.86 kg	5.91 kg

LG.




KG

Longueur Poids maxi utilisateur
Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers



Coulisseau doté d'un point fixe
Rope grab with a fixed point lock
Corredera provista de punto fijo
Guida a punto fisso
Gleitelement mit Festpunkt



Matière connecteur
Material of connector
Material conector
Materiale connettore
Material des Verbinders